DELLTM OPTIPLEXTM 755



ROBUST MAINSTREAM DESKTOP DESIGNED TO MEET YOUR NEEDS, NOW AND IN THE FUTURE



The new Dell OptiPlex 755 offers a compelling, versatile solution that can help you meet evolving business needs with the right technologies and services. Thanks to Dell's innovative approach to scalable remote client management, the OptiPlex 755 offers you a choice between several systems-management options. These options allow you to select an approach that's appropriate for your current infrastructure, while easily scaling to meet future needs. Options include:

- Widely installed ASF (Alert Standard Format) standards-based technology, which supports basic in- and out-of-band hardware inventory, alerting, and power control
- Intel® Active Management Technology (Intel AMT), which adds encrypted communications to ASF requirements, and also provides remote diagnosis and troubleshooting capabilities
- Intel® vPRO™ processor-based technology adds processor-specific security technologies to Intel AMT's functionality

In addition, Dell continues to expand our Deployment Services — now featuring ImageDirect options, a web-based tool that can enable you to build and apply your custom images for current and future systems. And because we know data security is a vital concern, the OptiPlex 755 offers optional RAID 1 support for real-time datamirroring protection. Plus, those who elect for a full vPRO platform can enjoy additional advanced security and remote remediation features.

- Your choice of flexible options from ASF 2.0 to Intel AMT 3.0, and even full Intel vPRO processor technology
- Standards-based management (DASH 1.0 and WS-MAN) help ensure simplicity and interoperability
- Dell Client Manager brings it all together in one management console

POWER EFFICIENCY: Productivity and power savings in a proven, reliable design

- Dell's unique approach to Energy Smart hardware and software — including Intel® Core™ 2 Duo processors, efficient management power settings, available 80+ power supplies and ENERGY STAR® 4.0 configurations
- Dell's online Energy Calculator indicates potential savings of up to 78% by choosing the most efficient configurations
- Dell is working alongside industry leaders and governments worldwide to help drive revolutionary change

SMART SECURITY: Strategic, comprehensive endpoint solutions for all types of businesses

- Intel vPro technology helps simplify asset inventory, isolation of virus-infected PCs, security patch deployment and more
- RAID 1 support helps keep data intact and accessible via real-time redundancy
- Built-in TPM 1.2 helps protect the network from unauthorized access, while enabling multi-factor authentication via optional Smart Card Reader and/or fingerprint reader

DELL DEPLOYMENT SERVICES: Image management, customization and deployment made easy

- Specific provisioning and pre-configured setting options for iAMT and Intel vPRO technology customers
- ImageDirect, a new web-based tool allowing you to create, manage and load your custom images to Dell client systems
- Microsoft® Windows Vista® Assessment and Migration options help streamline and optimize your deployment processes







ELLTM OPTIPLEXTM 755

- Intel® Core™ 2 Quad - 1066MHz FSB, LGA 775, 8MB L2 cache, Intel® VT, Enhanced Intel SpeedStep® Technology, Intel® 64 and Execute Disable Bit (Q6xxx series) **Processor Type**

- Intel® Core™ 2 Duo - 1333MHz FSB, LGA 775, 4MB L2 cache, Intel® vPro™ Technology, Intel® VT, Intel® TXT, Enhanced Intel SpeedStep® Technology, Intel® 64 and Execute Disable Bit (E6x50 series)

- Intel® CoreTM 2 Duo - 1066MHz FSB, LGA 775, 4MB L2 cache, Intel® VT, Enhanced Intel SpeedStep® Technology, Intel® 64 and Execute Disable Bit (E6x20 series)

- Intel® Core™ 2 Duo - 800MHz FSB, LGA 775, 2MB L2 cache, Enhanced Intel SpeedStep® Technology, Intel® 64 and Execute Disable Bit (E4000 series)

- Intel® Pentium®- 800MHz FSB, LGA 775, 1MB L2 cache, Enhanced Intel SpeedStep® Technology, Intel® 64 and Execute Disable Bit (E2000 series)

- Intel® Celeron®- 800MHz FSB, LGA 775, 512MB L2 cache, Intel® 64 and Execute Disable Bit

Chipset Intel® Q35 Express Chipset (ICH9DO)

Dell recommends Microsoft® Windows® XP Professional; Microsoft Windows XP Home Edition; Microsoft® Windows Vista® Home Basic; Microsoft® Windows Vista® Business; Microsoft® W **Operating Systems**

Windows Vista® Ultimate

Video Intel® Graphics Media Accelerator 3100°; DVI Adapter card; 128MB ATI Radeon™ X1300 with DVI and TV-out; 256MB ATI Radeon HD 2400 PRO w/DVI AND w/DVI

XT Dual monitor DVI/VGA via cables, TV-out

Up to four DIMM slots (2 in USFF chassis); Non-ECC dual channel 2DDR2 SDRAM3, supporting 512MB to 8GB4 (except on USFF) Memory

-Supports 667 MHz up to 8GB4

-Supports 800 MHz up to 4GB4 (please note USFF does not support 800MHz)

Networking Intel® 82566DM Gigabit⁵ LAN 10/100/1000

Standard I/O Ports 9 USB 2.0 (2 front, 6 rear, 1 internal), USFF offers 7 USB 2.0 (2 front, 5 rear), 1 Ethernet (RJ45), 1 serial (9-pin) (16550 compatible), 1 parallel (25-hole, bi-directional),

1 VGA out (15-hole), 1 DVI-I out (USFF) 28-hole DVI connector, optional add-in PS2 card with second serial port (not available on USFF), 1 stereo line-in, 1 microphone-in,

1 speakers/line-out, 1 headphone (front), optional add-in external SATA card with SATA port (not available on USFF)

Hard Drive 80GB, 160GB and 250GB⁶ 7200RPM SATA II, 3.0GB/s and 80GB⁴ 10K RPM SATA II 3.0GB/s

CHASSIS

Dimensions Minitower: Desktop: **Small Form Factor: Ultra Small Form Factor:** 16.10" x 7.36" x 17.52" 15.65" x 4.59" x 14.25" 12.45" x 3.65" x 13.4" 10.3" x 3.5" x 9.9" $(H \times W \times D)$ (40.89cm x 18.69cm x 44.50cm) (39.75cm x 11.66cm x 36.19cm) (31.63cm x 9.26cm x 34cm) (26.3cm x 8.9cm x 25.28cm) **Number of Bays** 2 internal 3.5" 1 internal 3.5" 1 internal 3.5" 1 internal hard drive 1 external 3.5" 1 external 3.5" 1 external 3.5" (slimline) 1 external removeable drive 2 external 5.25" 1 external 5.25' 1 external 5.25" (slimline) 2 full height PCI 2 low-profile PCI 1 internal hard drive **Expansion Slots** 1 low-profile PCI 1 low-profile PCle x 16 graphics 1 PCle x 16 full height graphics 1 low-profile PCle x 16 graphics 1 external removeable drive (Optional riser converts the PCle and PCl to either 1 PCle and 1 PCl or 2 PCl, full height)

Power Supply Minitower 305W; Desktop 280W; Small Form Factor 275W; Ultra Small Form Factor 220W

PERIPHERALS

CRT: Dell 17" E773 CRT, analog; Dell 17" E773 CRT, analog; speakers Monitors

Flat Panel Analog: Dell 15" ET57FP Flat Panel, analog; Dell 17" E177FP Flat Panel, analog; Dell 17" E178FP Flat Panel, analog; Dell 19" E198FP Flat Panel, analog; Dell 19" E1 Widescreen Flat Panel Analog: Dell 19" E198WFP Widescreen Flat Panel, analog; Dell 20" E207WFP Widescreen Flat Panel, analog; Dell 22" E228WFP Widescreen Flat Panel, analog UltraSharp Digital Flat Panel: Dell 17" UltraSharp 1707FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 19" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 19" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VGA/DVI; Dell 10" UltraSharp 1907FPV Flat Panel, VA, adjustable stand, VA, adjustable stand, VA, adjustable

Kevboard Dell USB keyboard, no hot keys; Dell USB Enhanced Multimedia keyboard; Smart Card Reader USB keyboard; Bluetooth® keyboard and mouse

Dell USB two-button and Dell USB optical two-button scroll, Dell USB Premium five-button Mouse

Internal Dell Business audio speaker, Dell A225, Dell A525, AS501 and AS501PA sound bar available with select FP monitors **Speakers**

STORAGE DEVICES

Removeable Media Storage Devices

USB floppy drive, CD-ROM, CD-RW/DVD combo, DVD-ROM7 and DVD+/-RW8

SECURITY

ASSY Trust Suite, Chassis loop lock support (with cable locks available), Chassis intrusion switch, Setup/BIOS Password, I/O Interface Security, Smart Card and Bio-metric readers, Intel vPro Security

Circuit Breaker technology, Intel® Trusted Execution Technology and VT-d

SYSTEMS MANAGEMENT

Hardware Management Options

No Management (Management Disabled) ASF 2.0 (Legacy Systems Management), iAMT 3.0, Intel vPRO

Dell Client Manager

A no-charge download of a single hardware management console allows you to deploy, manage and troubleshoot Dell client systems across your entire organization. Optional upgrades to Standard Dell Client Manager Plus or the Management Suite for Dell Clients available. Altiris® Manageability Toolkit™ required to support advanced Intel® vPro™ Technology features, sold separately

ENVIRONMENTAL, ERGONOMICS AND REGULATORY, SERVICE AND SUPPORT

Blue Angel, CECP, E-star 4.0, TCO 05, WEE, Japan Energy Law, CES, Japan Green PC, FEMP, South Korea Eco-label, EU RoHS9, China RoHS, EPEAT **Standards**

Base Service Three-Year Next Business Day On-Site

Optional Service Custom Factory Integration (CFI), Gold Technical Support (GTS), Same Day Response (12x5), On-Site Hardware Support, CompleteCare™ Accidental Damage, PC Installation Services, Dell

Training, Asset Recovery Services

^{7.} DVD-ROM drives may have write-capable hardware that has been disabled via firmware modifications.

8. Disss bumed with this drive may not be compatible with some existing drives and players; using DVD-R media provides maximum compatiblity.

9. Meets the requirements of the EU Directive on the restriction of the use of certain Hazardous Substances dated January 27, 2003.

10. For a copy of our guarantees or limited warranties, please write Dell USA L.P., Attr. Warranties, One Dell Way, Nound Rock, TX 78682. For more information, visit www.dell.com/warranty.

11. Service may be provided by third-party. Fechnician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract.

Dell, the Dell logo, OptiPlex are trademarks of Dell Inc. Intel, Core, Pentium, Celeron and SpeedStep are trademarks or registered trademarks of Intel Corporation. Microsoft, Windows and Windows Vista are registered trademarks or trademarks of Microsoft Corporation. Altris and Manageability Tool Kit are registered trademarks or trademarks of Advanced Micro Devices, Inc. Bluetooth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetoth is a registered trademark of Bluetom or Advanced Micro Devices, Inc. Bluetom or Advanced Micro Reproduction or distribution in any manner whatsoever without the express written permission of Dell Inc. is strictly forbidden.



^{1.} Up to 256MB of system memory may be allocated to support integrated graphics, depending on system memory size and other factors.
2. Dual-channel memory requires two each of the same capacity memory DIMMs.
3. Your graphics solution may use a portion of your system memory to support graphics depending on your operating system, system memory size and other factors.
4. The total amount of usable memory available will be less than 4GB, depending on the actual system configuration. To utilize more than 4GB of memory requires a 64-bit OS.
5. This term does not connote an actual operating speed of 1 GB/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.
6. For hard drives, GB means 1 billion bytes; actual capacity varies with preloaded material and operating system and will be less.
7. DVD-ROM drives may have write-capable hardware that has been disabled via firmware modifications.
8. Discs burned with this drive may not be compatible with some existing drivings and players; using DVD-RB media provides maximum connectibility.